

Burkina Faso Overseas Warehouse Low-Power Optical Module 800G



Overview

It is compliant with IEEE 802.3 800GBASE-VR8 and OSFP MSA module requirements with integrated heat sink. Optical signals are carried over eight pairs of parallel lanes, with one wavelength per lane.

Article Content

Cisco OSFP 800G Transceiver Modules Data Sheet

It is compliant with IEEE 802.3 800GBASE-VR8 and OSFP MSA module requirements with integrated heat sink. Optical signals are carried over eight pairs of parallel lanes, with one wavelength per lane.

Demo: CEI OSFP 800G SR8 LPO Optical Transceiver Module

OSFP 800G 2xFR4 LPO Optical Transceiver Module 2 sets of 400Gbps FR4, data rate up to 53.125GBaud per channel Typical Power Consumption less than 10W Up to 2km reach with Single

800G/600G/400G OSFP Digital Coherent Optics

The 800G Digital Coherent Optics (DCO) family of transceivers are available in two small form-factors, QSFP-DD and OSFP, which enable them to plug directly into

800G OSFP-Product Solutions-INNOLIGHT

800G OSFP optical module includes two architecture solutions, 4x100Gx2 and 8X100G. In addition to the traditional EML design, it also adopts silicon-based solution to meet short-distance transmission

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: <https://metramarket.es>

Technical inquiry: <https://metramarket.es/contact.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

