


Dimensions of a 1U Standard Chassis for Vehicle-Mounted Fiber Optic Cables



Overview

■ Dimensions [H x W x D]: 1U - 44. 5x485x180 mm, 3U - 133x485x180 mm, ■ Color: RAL7035 (light grey) glossy, other colors on request, ■ Chassis 1U holds 3 LGX-S modules (single), ■ Chassis 2U holds 6 LGX-S modules (single) or 3 LGX-D modules (double), ■ Dimensions [H x W x D]: 1U - 44. Supports up to 12 single or 6 double modules, supports 72 ports per 1U, compatible with EDR, features front/rear module fitting and horizontal opening front door. Chassis ODF DIN 1U Q-Fiber is a rack box designed for mounting in a data communication cabinet by means of rack bolts. Network test access points (TAPs) are hardware tools that allow you to access and monitor your network. The passive fiber modular chassis system supports 1Gbps, 10Gbps, 25Gbps, 40Gbps, 100Gbps, 400Gbps, and 800Gbps network speeds. CommScope® EHD-1U is an EHD Series fiber VAM panel built as an empty, sliding 1RU chassis for standard 19 in racks. Finished in black, the chassis measures.



Article Content

Chassis ODF DIN 1U Q-Fiber

Chassis ODF DIN 1U Q-Fiber is a rack box designed for mounting in a data communication cabinet by means of rack bolts. It has been designed to hold one (in the 10" option) or three (in the 19" option)

SelectTAP Fiber Modular Chassis

Fits into a standard 19 inch rack and accommodates multiple TAP modules:
Dimensions: 17.40" Width x 1.75" Height x 13.45" Depth. Multiple modules are offered for the SelectTAP Platform. Modules are

Chassis LGX Q-Fiber

Dimensions [H x W x D]: 1U - 44.5x485x180 mm, 2U - 88.5x485x180 mm, 3U - 133x485x180 mm, Color: RAL7035 (light grey) glossy, other colors on request, Chassis 1U holds 3 LGX-S modules (single),

760209940 | HD-1U

High Density 1U modular cassette sliding Panel, accepts (4) G2 modules or MPO panels, providing up to 48 duplex LC ports, or up to 32 MPO ports

CommScope EHD-1U Industrial Cable 1RU Empty Chassis

It accepts single high standard NG4 modules and ships UNLOADED with an unloaded front interface and 0 total ports for custom configurations. Finished in black, the chassis measures 342.9 mm | 13.5

FHD-1UFMT-N Rack Mount Fiber Enclosure Datasheet | FS

Enclosure meets the TIA/EIA-568-C.3 Standard on the performance requirements of fiber distribution devices. Compared with the last generation, it has been upgraded to simplify the operation, the top

Q-Series Rackmount Enclosure | Fiber Enclosure Systems

The 1U Q-Series Standard Density (SD) footprint fiber enclosure system is designed to support standard density applications in building networks. The all-steel chassis enables reliable

Fiberdyne Labs, Inc. 1U FiberPass HD Cassette Chassis

Fiberdyne Labs, Inc. 1U FiberPass HD Cassette Chassis is designed to support Ultra High Density fiber distribution environments; including Data Centers, Cell Tower Shelters and Central Office

What Are 1U Server Rack Dimensions? Height, Width & Depth Guide

You'll get precise, actionable 1U server rack dimensions — including height (1.75" / 44.45 mm), width (19" / 482.6 mm), and critical depth considerations (20-40+ inches, with usable depth

IANOS Standard chassis 1U

Efficiently manage fiber cables with the High-Density IANOS Chassis (1U). Supports up to 12 single or 6 double modules, supports 72 ports per 1U, compatible with EDR, features front/rear module fitting

24-48 Port Specification Grade Fiber Enclosure, 1U - Unloaded

The Specification Grade Fiber Optic Enclosure is a configurable rack mount unit for storing and terminating incoming fiber cable. The enclosure may be configured with ModLink Cassettes, 6-Pak

1U Slide-out Rack Mount Fiber Enclosure Datasheet | FS

Features Up to 144 fibers in 1U space. Sliding drawer is ideal for panel access management. Offers total front access to all patch cords and rear cables for in-cabinet mounting locations. Mounts to standard

Rack-mount chassis for 4 high-density fiber or copper cassettes, 1U

Insert up to four N484-Series copper and/or fiber cassettes (sold separately) into this cost-effective enclosure panel. Mounting in just 1U of space in an EIA-standard 19-inch rack, the compact N484

FCR-X Series Fiber Rack Mount Enclosure, 1U, 3 LGX Panels

FCR-X Series Fiber Rack Mount Enclosure, 1U, 3 LGX Panels, Horizontal, Unloaded The FCR-X fiber rack-mount enclosure is a passive optical assembly that guarantee highly reliable performance

FHU Fiber Patch Panel Datasheet | FS

LC or SC connectors to offer an economical, high-density fiber termination solution that doesn't take up much space. These ultra-compact patch panels mount easily in any standard 19" rack or cabinet to

UHD Chassis Spec Sheet

Overview PPC's Ultra-High Density (UHD) Chassis is a modular, standards-based, pre-terminated distribution platform designed to increase port density, improve connector access, and efficiently

Data Center Racks, Cabinets, and Cages: An In-Depth

Inside a data center, a labyrinth of servers and high-tech networking gear are arranged in specialized racks, secure cabinets, and impenetrable cages.

1U 19" Rack Mount Fiber Optic Box Enclosure with LGX

About this item 1.Rack Mount Fiber Enclosure: 19" Fiber Optic Enclosure Box with 1 Splice Tray and Spool. This secure fiber termination box fits 19" rack cabinets

Contact Us

Continue your research online:

Website: <https://metramarket.es>

Technical inquiry: <https://metramarket.es/contact.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

