Fiber Optic Sensor Adjustment Knob



Overview

Tri-Tronics Fiber Optic Sensor, SEWLKF1 Mark II Tri-Tronics fiber optic sensor SEWLKF1 SMARTYEYE® MARK II with White LED, knob adjustment, 4-wire M12 Conne.

Key Takeaways

A fiber optic sensor with a knob allows easy on-site sensitivity adjustment for precise detection of objects, including small or transparent targets, in industrial applications.

Overview

A fiber optic sensor is a high-precision detection device that uses light transmitted through optical fibers to detect the presence, position, size, or movement of objects. The sensor typically consists of two main components: the amplifier, which contains the light source and processing electronics, and the fiber optic cable or head, which transmits and receives light signals. Knob-type sensors feature a manual adjustment knob on the amplifier, enabling quick and intuitive tuning of sensitivity or detection thresholds directly on-site without additional tools.

Key Features

Knob Sensitivity Adjustment: Allows fine-tuning of detection sensitivity for small, transparent, or reflective objects, making setup fast and user-friendly.

High-

Speed Performance: Provides rapid response suitable for fast-moving production lines.

© 2026 METRA FIBER MARKET - All rights reserved

Anti-

Interference Capability: Optimized circuitry reduces electrical noise and ensures stable operation in industrial environments. Adjustable Delay Function: Enhances signal reliability by allowing a delay in output response, useful for filtering transient signals. Compatibility: Works with standard fiber optic cables and supports multiple detection modes, including diffuse, reflective, and through-beam configurations.

Output Options: Typically supports NPN or PNP output modes, with protection against reverse polarity, short circuits, and overloads. Power Supply: Operates on 12–24 VDC, suitable for most industrial automation systems.

Applications

Fiber optic sensors with knob adjustments are widely used in industrial automation, including: Packaging lines: Detecting labels, edges, or part presence. Electronics manufacturing: Monitoring small components or transparent materials. Robotics and precision machinery: Ensuring accurate positioning and movement detection.

Harsh or tight environments: The fiber head can be installed in areas where conventional sensors cannot fit or withstand high temperatures, dust, or vibration.

Practical Advantages

The knob adjustment simplifies calibration, allowing operators to quickly adapt the sensor to different targets or environmental conditions without complex programming. This flexibility reduces downtime and improves reliability in automated processes. Additionally, modular designs and compatibility with PLCs or automation controllers make these sensors versatile for various industrial setups.

In summary, a fiber optic sensor with a knob combines precision detection, fast response, and easy on-site adjustment, making it ideal for applications requiring high accuracy and adaptability in challenging industrial environments.

Article Content

Tri-Tronics Fiber Optic Sensor, SEWLKF1 Mark II Smarteye

Tri-Tronics fiber optic sensor SEWLKF1 SMARTYEYE® MARK II with White LED, knob adjustment, 4-wire M12 Connector and F1 Fiberoptic Optical Block. 12 to 24 VDC Supply Voltage, polarity

Search results for: Knobs Fiber Optic Sensors – Mouser

All Products Sensors Optical Sensors Fiber Optic Sensors Share Show other information about "Knobs" See related content »

TRI-TRONICS SEIKF1 12-24 VDC Supply Voltage, 4-Wire, F1

© 2026 METRA FIBER MARKET - All rights reserved

Product Description 12-24 VDC SUPPLY VOLTAGE, 4-WIRE, F1 FIBEROPTIC OPTICAL BLOCK., FIBER OPTIC SENSOR, KNOB ADJUSTMENT, M12 CONNECTOR, MARK II, MAXIMUM RANGE

Fiber Optic Sensors | KEYENCE America

These are reliable and easy-to-use devices that have high power, can automatically adjust to real-time conditions, and have a straightforward display that eliminates

FS-N Series Sensor Setting Guide | PDF | Equipment

This document provides instructions for setting sensitivity and calibrating digital fiber optic sensors. It describes several calibration methods including two-point

Tri-Tronics CMSWL-2BF1 Colormark II Fiber Optic Sensor 18483

Adapts a sensor to any standard fiber optic light guide with .187" O.D. tips. The light guide is inserted and held in place with a slide-action snap. Contact: Industrial Sensors and Controls 615-471-1013,

Panasonic FX-412 Digital Fiber Optic Sensor with Multi-Turn

Unique design with multi-turn pot and digital display of threshold and incident light level. Four levels of light emissionto eliminate saturation. Peak/Hold function.

FIBER-OPTIC SENSORS

Construction Standard fiber: Most fiber optic sensing heads use this configuration of fiber (i.e. a single fiber covered by a protective sheath). The fibers are usually plastic, 0.5 to 1 mm in diameter and

Panasonic FX-412 Digital Fiber Optic Sensor with Multi-Turn

Panasonic FX-412 Digital Fiber Optic Sensor with Multi-Turn Sensitivity Adjustment Knob - Green LED - NPN Panasonic (formerly Sunx) digital display amplifier with easy to use multi-turn sensitivity

Optical Fibre-Based Sensors—An Assessment of Current Innovations

Optical fibre sensors are an essential subset of optical fibre technology, designed specifically for sensing and measuring several physical parameters. These sensors offer unique advantages over traditional

How to adjust photoelectric sensor sensitivity

1. Sensitivity adjustment knob: Many photoelectric sensors are equipped with a sensitivity adjustment knob or button, which can be used to adjust the sensitivity of the sensor. By turning or

Recent advances of optical fiber biosensors based on surface

© 2026 METRA FIBER MARKET - All rights reserved

Optical fiber biosensors based on the surface plasmon resonance (SPR) phenomenon are generating increasing interest due to their capability of real-time monitoring of analytes in a

FS-N Series Setting Guide 468GB

The light transmission level and light intensity sensitivity are automatically adjusted with simple operation. This function is effective when the intensity value does not change (saturation) from the

Fiber Optic Sensor : Types, Working, Interfacing & Its Applications

The fiber optic sensor working principle is that transducer changes some optical fiber system parameters like wavelength, intensity, phase, polarization, etc. This gives an increase in

What is a Fiber Optic Sensor?

A fiber optic sensor operates with an optical fiber cable connected to a dedicated light source. These sensors offer great mounting flexibility and can be used is in a variety of environments.

Fiber Optic Sensors | KEYENCE America

Fiber optic sensors are compact because the detection circuit is located in the amplifier, allowing for detection even in narrow spaces. Installation and

Keyence Fiber Optic Sensor Setup: A Quick Guide

Understanding Keyence Fiber Optic Sensors Before diving into the setup, let''s understand what these sensors are all about. Keyence fiber optic sensors are designed to detect the presence or

Tri-Tronics CMSWL-2BF1 Colormark II Fiber Optic Sensor 18483

Tri-Tronics CMSWL-2BF1 COLORMARK™ II, No Pulse Stretcher, White LED, F1 Optical Block. 12-24 VDC polarity protected. Fiberoptic. Maximum Sensing Range is depending on fiber optics. 18483

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

© 2026 METRA FIBER MARKET - All rights reserved

Contact Us

Continue your research online:

Website: https://metramarket.es
Technical inquiry: https://metramarket.es/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 METRA FIBER MARKET - All rights reserved