Industrial Switch Card Slot Location



Overview

PLC-5 I/O addressing explained: learn to identify physical slot locations from I/O addresses. Covers 1-slot, 2-slot, and half-slot modes with S2 status file verification.

Key Takeaways

Industrial switch card slots are typically arranged in a chassis or cardcage, with each slot numbered sequentially and equipped with top and bottom connectors for power and signal connections.

Cisco I

E 4010 SwitchThe Cisco IE 4010 series provides rugged industrial Ethernet switching. While the exact slot layout depends on the model, the switch generally has modular ports and field-replaceable components. The card slots are located on the cable side of the switch, allowing easy access for Ethernet connections and module replacement.

Each slot supports autonegotiation for speed and duplex settings, and the switch can accommodate redundant AC or DC power supplies for reliability in industrial environments.

N



© 2026 METRA FIBER MARKET - All rights reserved

I SwitchBlockFor National Instruments SwitchBlock systems, the card slots are installed in a chassis, and each slot is designed to accept a SwitchBlock card. The chassis must be properly configured and connected to a controller before inserting cards. Slot numbering corresponds to the physical position in the chassis, and proper shielding and cable length (maximum 30 m) are required to maintain EMC compliance.

Allen-

Bradley PLCsIn Allen-Bradley PLCs, such as the SLC 500 series, slots are numbered sequentially starting from 0 or 1, depending on the system. Each slot corresponds to a module, and the slot number is used in addressing inputs and outputs. For example, a digital input in slot 4 would be addressed as I: 4/0, where 4 indicates the slot number and 0 the first input on that module.

This physical-to-logical mapping ensures correct communication between the PLC processor and the modules. Siemens CC-5 and CC-2 CardcagesSiemens CC-5 and CC-2 cardcages provide a central mounting point for system circuit card assemblies. The CC-5 has five slots, and the CC-2 has two slots, each occupying specific positions on the backbox studs or optional mounting plates.

Each slot has two removable terminal block connectors at the top for external equipment (labeled 1–16) and one at the bottom for internal power (labeled 17–24). Cards are inserted vertically, and power is applied through the bottom connector, while signal connections are made at the top.

General Guidelines

Slot numbering is sequential and often starts from the leftmost position in the chassis. Top connectors are typically used for field wiring or signal connections. Bottom connectors supply internal power or communication buses.

Physical access should allow easy insertion and removal of cards without disturbing adjacent modules. Documentation for each system should be consulted for exact slot layout, numbering, and connector pin assignments. Understanding the slot layout is crucial for proper installation, addressing, and maintenance of industrial switches and PLC modules, ensuring reliable operation in industrial environments.

© 2026 METRA FIBER MARKET - All rights reserved

Article Content

Cisco IE 4010 Switch Hardware Installation Guide

The slot for the flash memory card is on the front of the switch. The flash card is hot swappable and can be accessed on the front panel in non

PLC-5 Slot Addressing: Find I/O Location from Address – Industrial ...

PLC-5 I/O addressing explained: learn to identify physical slot locations from I/O addresses. Covers 1-slot, 2-slot, and half-slot modes with S2 status file verification.

Cisco IE 3000 Series Switch Hardware Installation Guide

When determining where to place the switch, observe these guidelines. Review these environmental and enclosure guidelines before

CC-5andCC-2r6_10-31-17_DRAFT.pmd

The Model CC-5 Cardcage from Siemens Industry, Inc., (see Figure 1) has five card slots and occupies two positions on the studs in the backbox or on the optional CAB-MP Mounting Plate.

PLC-5 Addressing for Inputs and Outputs

PLC-5 Addressing using 1-slot, 2-slot, and 1/2 slot addressing to determine the address of any I/O point on a local or remote chassis.

Installation Instructions Model HUB-4

The Model HUB-4 Communication Card from Siemens Industry, Inc., mounts in the CC-5 Card Cage and provides up to four independent data channels, which can be wired as either Style 4 or Style 7.

Overview of Allen Bradley PLC Address Mapping

The input address above may be connected to some type of discrete input unit, such as a toggle switch or a push-button. The output address may be connected to some discrete output unit,

Allen-Bradley Remote I/O Interface Card

Make Connections to I/O 1. Wire the 6-pin female connector provided with the interface card, as shown in figure 2, and attach it to the card''s connector.

Memory Maps and I/O Addressing | Basics of

Addressing the seventh bit (bit number 6) on a discrete output card plugged into slot 3 would require the label O:3/6. In either case, the numerical structure of that

© 2026 METRA FIBER MARKET - All rights reserved

How to address the I/O of Allen Bradley PLC''s?

SLC I/O are addressed by slot number. Example: I:1/15 would be last (16th) point in slot 1. There is no rack number involved. All addresses are

Eaton X Slot Industrial Relay Card Installation Instruction

Industrial Relay Card (IRC) 164201433 Rev C00 The Industrial Relay Card (IRC) indicates the operating status of the UPS system using the customer''s monitoring equipment. To install the IRC: 1. Verify

Guidelines for PLC installation, wiring and connection

Check the slot location according to the I/O address assignment document. Loosen all terminal screws on each I/O module. Locate the wire bundle corresponding to

Memory Maps and I/O Addressing | Basics of

The IEC 61131-3 programming standard refers to this channel-based addressing of I/O data points as direct addressing. A synonym for direct addressing is absolute

Eaton Industrial Gateway Card Mini-Slot for UPS Systems | Eaton

The INDGW-M2 Gigabit Industrial Gateway Mini-Slot card meets both UL 2900-1 and IEC 62443-4-2 cybersecurity standards, empowering IT professionals with superior Gigabit speed, capabilities and

Where Is Nintendo Switch SD Card Slot?

Each version of Nintendo Switch has its own dedicated SD card slot. Adding a microSD card to your Switch is pretty easy. You will find the Nintendo Switch memory card slot at the back

Switch 2 SD Card Slot Location Guide

That does, sadly mean that any games stored on an older microSD card in your Switch won''t be playable if you plug it into your Nintendo Switch 2. That''s all you need to know about the

Industry Standard Architecture

PCI slots are rotated compared to their ISA counterparts — PCI cards were essentially inserted upside-down, allowing ISA and PCI connectors to squeeze

Cisco IE 3100 switch installation materials and tools

Secure Digital (SD) flash memory module (SD card) preloaded with the IE 3100 software and switch configuration files Small Phillips-head screwdriver for opening the SD card slot Large

© 2026 METRA FIBER MARKET - All rights reserved

Contact Us

Continue your research online:

Website: https://metramarket.es
Technical inquiry: https://metramarket.es/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 METRA FIBER MARKET - All rights reserved