Is the encoder cable routed through the low-voltage cable tray



Overview

Encoder Feedback Cable Routing for EMI ReductionYes, the encoder feedback cable is typically routed separately from power cables to reduce electromagnetic.

Key Takeaways

Encoder cables should generally not be routed through the same low-voltage cable tray as power cables to minimize electromagnetic interference (EMI) and ensure signal integrity.

Best Practices for Encoder Cable Routing

Separation from Power Cables: Encoder feedback cables carry low-voltage, low-current signals that are highly susceptible to EMI from nearby power cables, especially those supplying motors or high-current loads. To reduce noise, encoder cables should be routed separately from power cables, maintaining a recommended separation distance of 6–12 inches (15–30 cm) whenever possible. If crossing is unavoidable, it should be done at a 90-degree angle to minimize coupling.

Shielding and Grounding: Encoder cables should be shielded, with the shield typically grounded at the controller side. Twisted-pair wiring and individually shielded wires can further enhance noise immunity, particularly in high-noise environments. Cable Tray Considerations: While low-voltage cable trays are used for control and communication wiring, encoder cables should ideally have their own dedicated tray or conduit.

© 2026 METRA FIBER MARKET - All rights reserved

Running encoder cables in the same tray as power cables is discouraged because it increases the risk of signal degradation and false readings. Standards Compliance: Industry standards such as IEC 60204-1 and NFPA 79 recommend separate routing for signal and power cables in industrial environments to ensure reliable operation and minimize EMI. Additional Recommendations: For long cable runs, use high-quality, low-capacitance, shielded twisted-pair cables.

Differential encoders with complementary channels (A,/A, B,/B, Z,/Z) can further reduce susceptibility to noise. Fiber optic solutions may be considered for extreme distances or high-noise environments.

Conclusion

Routing encoder cables through a low-voltage cable tray shared with power cables is not recommended. For optimal performance and reliability, encoder cables should be routed separately, shielded, and grounded according to manufacturer guidelines and industry standards. This approach ensures accurate signal transmission and minimizes the risk of EMI-induced errors.

Article Content

Encoder Feedback Cable Routing for EMI Reduction

Yes, the encoder feedback cable is typically routed separately from power cables to reduce electromagnetic interference (EMI). Technical rationale: Encoder feedback cables carry low

Encoder Wiring Best Practices

Encoder cabling should be run in conduits, preferably separate from other wires. If this is not possible, they should be run only with other low-power DC cables.

Cable Separation Standards

Why It Matters: High-voltage and limited energy circuits routed too closely can cause cross-talk, distortion, or packet errors, especially in dense cable trays or congested ceiling spaces.

Technical Guidelines for Cable Tray Installation and

Segregation of Power and Signal Cables: Power (high-voltage) and signal (low-voltage) cables should be routed separately, using dedicated trays to minimize

Good practice rules for electromagnetic compatibility (EMC) of LV

Essential components in the installation, metal cable tray and prefabricated trunking contribute to the control of EMC in several ways. First, they constitute a common, continuous and

© 2026 METRA FIBER MARKET - All rights reserved

Core Principles for Electrical and Instrumentation Cable Tray Layouts

Layered Separation: Strong current and high-voltage cables are positioned apart from low-current, low-voltage instrumentation cables. Layered separation reduces interference, preserving the quality of

How to specify encoder cables

To specify the best encoder cable for an application, factors such as output type required and cable length should be considered. An encoder cable transmits encoder output, which may

Checking for Encoder Cable Cross-Talk or Interference

Learn how to identify and mitigate cross-talk or interference on encoder cables routed near power lines through visual inspection, oscilloscope measurements, signal quality analysis, and

Encoder Cables | How To Specify The Right Cable

How to specific the right encoder cable based on encoder type to avoid signal noise, cross talk and tips for running longer encoder cables. Learn more here!

Avoiding Mistakes in Instrumentation Cable Tray ...

One of the worst mistakes you can make on an EPC project is to run low-voltage instrumentation cables and high-voltage power cables in the same tray. This causes inductive

Cable Trays

Cable trays distribute bundles of electrical cables from power supplies to electrical equipment and components throughout the plant. Cable tray systems consist of insulated electrical cables layered

Cable Cleats in BESS: Why Above-Ground Power Routing is

As BESS installations move above ground to reduce trenching and improve thermal performance, cable restraint becomes safety-critical. Learn why cable cleats are used, where they

High Temperature Cable Guide: Insulation Types, Ratings & Selection

High temperature tray cable constructions using XLPE, ETFE, or FEP insulation are specified for industrial environments where cable trays run through hot areas — near boilers, process equipment,

Yaskawa SGMGH-09DCA6F-OY AC Servo Motor

© 2026 METRA FIBER MARKET - All rights reserved

Yaskawa SGMGH-09DCA6F-OY: Request a quote now. Quality & reliability ensured through automated testing

Good practice rules for electromagnetic compatibility

1. Electrical continuity of cable trays Where it is correctly inter-connected and connected to the installation''s general equipotential link, metal

How to specify encoder cables

For differential encoder signals, a twisted pair of cables can carry the encoder signal and its complement. Without special consideration to encoder

Mixing Communication cables in the same cable tray or raceway

Yes, as long as these communications cables are all low voltage DC. Do not mix Control and AC power lines with low voltage communication cables in the same raceway. These

General Cable Routing Description

Also, cables may be routed through a cable tray that is installed on the top of the cabinet. The specifications, routing, cross-section, and location for cable routing should be predetermined, and the

Contact Us

Continue your research online:

Website: https://metramarket.es
Technical inquiry: https://metramarket.es/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 METRA FIBER MARKET - All rights reserved