The parameters of an optocoupler are



Overview

Optocoupler Working Principle: Types, CTR Formula and Industrial. The Current Transfer Ratio is the parameter that tells you how efficiently the optocoup.

Key Takeaways

Key parameters of an optocoupler include current transfer ratio (CTR), isolation voltage, input/output voltage and current ratings, and switching times. Main Parameters1. Current Transfer Ratio (CTR): CTR is the ratio of the output current (phototransistor collector current, IC) to the input current (LED forward current, IF), expressed as a percentage.

It indicates the efficiency of signal transfer and is influenced by LED current, phototransistor voltage, ambient temperature, and aging.

Typical CT

R values for phototransistor outputs range from 50% to 150%, while Darlington outputs can reach 50% to 500%. 2. Isolation Voltage (Viso): This is the maximum voltage that can be applied between the input and output without causing dielectric breakdown.

Standard values range from 500 V to 5 kV RMS, depending on the device construction and application requirements. 3. Input (LED) Parameters: Forward Current (IF): Maximum continuous current allowed through the LED, typically 40–100 mA.

Forward Voltage (VF): Voltage drop across the LED when conducting, which increases with higher current or lower temperature. Reverse Voltage (VR): Maximum voltage the LED can withstand in reverse bias without significant leakage current. 4.

© 2026 METRA FIBER MARKET - All rights reserved

Output (Phototransistor) Parameters: Collector-Emitter Voltage (VCE): Maximum voltage across the phototransistor, usually 30–70 V.

Off-

State Collector Current (IC(OFF)): Leakage current when the LED is off, which increases with supply voltage and temperature. Collector Saturation Voltage (VCE(SAT)): Voltage drop across the phototransistor when fully conducting. 5.

Switching Characteristics: Rise Time (tr) and Fall Time (tf): Time for the output to switch from low to high and high to low, typically 2–5 microseconds for standard phototransistor optocouplers. These times determine the device's frequency response and bandwidth. 6.

Power Dissipation: The total energy the device can safely dissipate, which depends on LED forward current, forward voltage, and phototransistor collector current and voltage. Power dissipation decreases with increasing ambient temperature. 7.

Operating and Storage Temperature: Operating Temperature: Range in which the device functions properly, typically -55°C to +125°C. Storage Temperature: Range for safe storage without power, typically -65°C to +150°C. These parameters are critical for designing reliable circuits using optocouplers, ensuring proper signal isolation, timing, and electrical performance across varying operating conditions.

Article Content

Optocoupler Working Principle: Types, CTR Formula and Industrial ...

The Current Transfer Ratio is the parameter that tells you how efficiently the optocoupler transfers a current signal from input to output. It is defined as the ratio of the output collector current

ANO007 | Understanding Phototransistor Optocouplers

In order to design a functionally robust and reliable application with optocouplers, it is essential to understand not only the device''s main parameters and parasitic elements, but also their tolerances

Optocoupler Construction, Working, and important Parameters

Optocoupler parameters like CTR, isolation voltage, and timing are key for reliable circuit design performance.

Everything You Need to Know About Optocouplers in Electronics

Optocouplers are used in many electronic devices, from mobile electronics to household electronics. So, in this article, let''s learn more about optocouplers along with their basics, types,

© 2026 METRA FIBER MARKET - All rights reserved

Guidelines for Reading an Optocoupler Datasheet

Optocoupler devices are renowned for their high reliability in the areas of isolation and safety. The safety and insulation ratings table serves as a quick reference for all key parameters the device is qualified for.

Transistor Output Optocouplers Frequently Asked Questions (FAQs)

It describes the two main parameters of optocouplers and is obtained by dividing the output current of the transistor by the forward current of the emitting diode and converting the result in a percentage

The Ultimate Designer''s Guide to Optocouplers | ODG

Optocouplers create a safe electrical break between circuits. This protects sensitive parts from high voltages. The Current Transfer Ratio (CTR) shows how efficient an optocoupler is. It tells

Basic Components

Basic Components - Optocouplers An optocoupler is a device that integrates a light-emitting diode (LED) and a photodetector into a single package. Function of Optocouplers In an optocoupler, the primary

What are the parameters specific to photocoupler and photorelay

What are the parameters specific to photocoupler and photorelay optical isolation devices, transfer ratio (CTR), trigger LED current, and threshold input current? For transistor-output photocouplers, when

What Is Optocoupler and Its Application with Examples

Video: How an Optocoupler Works and Example Circuit ‖ Photocouplers, Opto-couplers & Opto-isolators These devices are known by a

What is an Optocoupler and How to Choose the Right

We will explore the basics of optocoupler selection and their functionality, helping you choose the right one for your electronics design. By understanding the

Transistor Output Optocouplers Frequently Asked Questions (FAQs)

3. Q: WHICH MAXIMUM PARAMETERS SHOULD BE TAKEN INTO CONSIDERATION WHEN USING A TRANSISTOR OUTPUT OPTOCOUPLER? A: The input of optocouplers is defined with the

Optocoupler specifications for circuit design | doEEEt

Optocoupler parameters like CTR, isolation voltage, and timing are key for reliable circuit design performance.

© 2026 METRA FIBER MARKET - All rights reserved

Explanation of Photocoupler / Optocoupler Specifications

General specifications for various usage environments including absolute maximum ratings and electrical characteristics are available for Renesas photocouplers.

What is an Optocoupler, Optoisolator, Photocoupler

Optocoupler and opto-isolator specifications There are several parameters and specifications that need to be taken into account when using opto-couplers and opto-isolators: Current transfer ratio, CTR:

Opto-isolator

Schematic diagram of an opto-isolator showing source of light (LED) on the left, dielectric barrier in the center, and sensor (phototransistor) on the right [note 1] An opto-isolator (also called an optocoupler,

Optocouplers, Part 2: Parameters and applications

Part 1 of this FAQ explored the basics of the optocoupler. This part looks at key parameters and some application examples. Q: What are the primary factors used when assessing

ANO007 | Understanding Phototransistor Optocouplers

Application Note Understanding Phototransistor Optocouplers ANO007 by Eleazar Falco 01. INTRODUCTION An optocoupler, also known as photocoupler or opto-isolator, is a device which

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

© 2026 METRA FIBER MARKET - All rights reserved

Contact Us

Continue your research online:

Website: https://metramarket.es
Technical inquiry: https://metramarket.es/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 METRA FIBER MARKET - All rights reserved