Upgraded version of AWG wavelength division multiplexer for IDC data centers



Overview

In this study, we designed and fabricated a 16-channel silica-based AWG featuring low transmission loss and channel spacing of 800 GHz, suitable for large-scale wavelength multiplexing and demultiplexing in the O-band under LWDM. With advancements in optical communication technology, the number of AWG output channels has rapidly increased. However, achieving high center frequency accuracy (CFA) for these. Enablence's Coarse Wavelength Division Multiplexing (CWDM) optical demultiplexer (DEMUX) combines a sophisticated arrayed waveguide grating (AWG) design with high quality fabrication. The AWG design provides extremely low loss, wide passbands, and high flatness. Close collaboration with our customers and our proven expertise across fiber, cable, and connectivity ensure you'll get solutions that are smarter, denser, faster, and easier.

Article Content

Design and fabrication of E-band silica based dense wavelength

In order to further increase the amount of data transmission, the 48-channel dense wavelength-division multiplexing (DWDM) technology has been developed.

Wavelength-Division Multiplexing (WDM)

Two types are available: integrated arrayed waveguide gratings (AWG), offering low cost, compact size, and precise ITU grid alignment; and discrete filter-based WDMs, providing greater flexibility to

© 2026 METRA FIBER MARKET - All rights reserved

High-Performance Wavelength Division Multiplexers Enabled by Co ...

Here, we develop a novel design approach that co-optimizes inverse-designed wavelength division multiplexers and distributed Bragg gratings to achieve ultra-low crosstalk without compromising

AWG multiplexers and demultiplexers for data center interconnection

NeoPhotonics Corporation introduces the new Arrayed Waveguide Grating (AWG) multiplexers and demultiplexers for high-capacity, high-speed coherent transmission systems.

Optimization Method for Center Frequency Accuracy of High ...

The causes of center frequency deviation are analyzed, and an optimization method is proposed to adjust the constraint relationship and geometric position of the output waveguides in

CWDM — Enablence

Enablence''s Coarse Wavelength Division Multiplexing (CWDM) optical demultiplexer (DEMUX) combines a sophisticated arrayed waveguide grating (AWG) design with high quality fabrication.

Ultra-Low-Crosstalk Silicon Arrayed-Waveguide Grating

A silicon arrayed-waveguide grating (AWG) with 1.6-nm channel spacing is proposed and realized with high performances for dense wavelength-division (de)multiplexing systems.

Wavelength Division Multiplexers (WDM) | Corning

Explore wavelength division multiplexers (WDM), their applications, and products and learn why Corning is the best choice for WDM.

Design and fabrication of LWDM AWG for data centers with

In this study, we designed and fabricated a 16-channel silica-based AWG featuring low transmission loss and channel spacing of 800 GHz, suitable for large-scale wavelength multiplexing and

Design of 4-channel AWG Multiplexer/demultiplexer for CWDM system ...

Based on the theory of light transmission, the relationships between structure parameters and optical performance of AWG chip are analyzed. Four-channel AWG MUX/DEMUX chips for

Wavelength-Division Multiplexing

© 2026 METRA FIBER MARKET - All rights reserved

Wavelength Division Multiplexing (WDM) is a multiplexing and transmission scheme in fiber-optical telecommunications where different wavelengths, emitted by several lasers, each carry dedicated

256-Channel 10-GHz AWG Demultiplexer for Ultra-Dense WDM

Abstract: In this paper, a 256-channel, 10-GHz arrayed waveguide gratings demultiplexer for ultra-dense wavelength division multiplexing was designed using an in-house developed tool

LWDM — Enablence

LWDM MUX About Enablence LAN Wavelength Division Multiplexing (LWDM) optical multiplexer (MUX) is available using our proprietary Vortex design. The

Receiver Integration with Arrayed Waveguide Gratings toward Multi ...

In particular, wavelength scalability and functionality through multi-wavelength integrated devices will be a key to promoting the spread of future innovative all-photonic networks . Here,

16-channel, 100 GHz colorless AWG for new generation optical networks

The AWG was designed for a central wavelength of 1.55 μm and simulated in the wavelength range between 1.5 μm and 1.6 μm. The AWG was designed using the specially

Dense Wavelength Division Multiplexing

5.1.1 Coarse wavelength-division multiplexing and dense wavelength-division multiplexing Wavelength-division multiplexing (WDM) enables multiple-shift usage of transmission fibers by transmitting a

Enhancing Data Center Optical Interconnect Networks with Wavelength ...

Conclusion Wavelength Division Multiplexing (WDM) systems have revolutionized data center optical interconnect networks, providing an effective solution for capacity expansion and

Athermal AWG DWDM Mux DeMux | Gigalight Datasheets

Description The Gigalight Athermal Arrayed Waveguide Grating (AAWG) Dense Wavelength Division Multiplexer (DWDM) based on silica on silicon technology is designed for ITU channel spacing

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

© 2026 METRA FIBER MARKET - All rights reserved

Contact Us

Continue your research online:

Website: https://metramarket.es
Technical inquiry: https://metramarket.es/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.



© 2026 METRA FIBER MARKET - All rights reserved